


**ENCLOSURE PARTS:**



K4 6 X 25mm SCREW X 2

**MATERIAL**

- Front Plate: ABS, UL 94V-0
- IDC plastic: PC, UL 94V-0
- IDC contact: Phosphor Bronze with 200u "Tin over 100u" Nickel undercoat
- Spring Wire: Phosphor Bronze with 50u "Gold over 100u" Nickel undercoat
- Temperature: -40°C ~ 70
- Humidity: 10% ~ 90% RH
- Front Socket: 750 mating cycles
- Idc block: 200 termination cycles

**ELECTRICAL**

- Current rating: 1.5 Amps
- Insulation resistance: 500 MOhm
- Contact resistance: 20 mOhm
- DC resistanc: 0.1 Ohm
- Dielectric withstanding voltage: 1000 V
- F Connector
- Voltage rating: AC 150V
- Withstanding voltage: AC 500V one minute
- Contact resistance: 5mΩ at DC 1A
- Impedance: 75Ω nominal
- VSWR: 1.2max.0-1, 500MHZ
- Insulation resistance: 500MΩ min at DC 500V

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	A			
	A			

COMMON TOLERANCE		SHEET	OF	ALL COPY RIGHTS RESERVED	
CLASS	A	SIZE	A4	DAN-CHIEF ENTERPRISE CO., LTD.	
DIMENSION	±0.05	DIA	mm	TITLE	
L <= 3	±0.1	SCALE	1:1	625B48-1V1F-XX	
3 < L <= 6	±0.05	DATE	2004.02.18	DRAWING NO.	B-180
6 < L <= 16	±0.1	DESIGN		DRAWN	CHECKED
16 < L <= 30	±0.1				
30 < L <= 120	±0.15				
120 < L <= 315	±0.2				