


NOTE:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
CONDUCTOR RESISTANCE: 3 OHMS MAX.
INSULATION RESISTANCE: 20M OHMS MIN.
HI-POT: DC300V 0.01SEC.
2. PACKING:

ROUND CABLE METHOD SEE "DETAIL A"			
	BAG TYPE	QTY	LABEL
SMALL	POLYBAG	1 CABLE	NONE
LARGE	POLYBAG	ALL	NONE
EACH LARGE POLYBAG IN AN OUTER CARTON			



PIN OUT			
P1	P2	P1	P2
HDMI M	HDMI M	HDMI M	HDMI M
1	1	13	13
2	3	15	15
3	2	16	16
4	4	17	17
6	6	18	18
5	5	19	19
7	7	14	14
9	9		
8	8		
10	10	SHELL	SHELL
12	12		
11	11		

5	2PCS	DC-HDMI	DUST COVER: HDMI MALE DUST COVER.
4	13g	PVC-GN-50	OVER MOLD: GREEN PVC 50P, UL94V-0.
3	13g	PVC-BU-50	OVER MOLD: BLUE PVC 50P, UL94V-0.
2	2SETS	HDMI-19MS	CONNECTOR: HDMI A MALE, SOLDER TYPE, GOLD PLATED 15u", GOLD PLATED FULL SHELL.
1	1PC	HDMI CABLE	CABLE: [(28AWGx1P+DRAIN+AL/MY)x4C+28AWGx7C]+PAPER+BRAID, UL20276, BLACK PVC JACKET, OD=6.0±0.15mm.
ITEM	Q'TY	PART NO.	DESCRIPTION
PART LIST			

Scale	X:X	All Copy Rights Reserved	
3rd Angle Projection			DAW-CHIEF-ENTERPRISE CO., LTD.
Unit	mm	Title	
Date	2008/3/14	HD-HD-M2-2M	
Tolerance			
~20	~50	~150	150~
±0.2	±0.4	±0.5	±1.5
ANGLE			
		Drawn by	Checked by
		Joanne	